

AMENDMENTS TO THE CLAIMS

1. (Currently Amended) A ~~sealing member~~ rolling bearing adapted to a rolling bearing, wherein said rolling bearing comprises an inner ring, an outer ring, and a plurality of rolling elements rotatably disposed therebetween and defines a space accommodating said rolling elements and having at least one end part opening opened in an axial direction thereof, and wherein the space is formed between the inner circumferential surface of the outer ring and the outer circumferential surface of the inner ring, said sealing member comprising:

a first portion substantially covering at least a part of the end part opening of the space;

and

a second portion being bonded and fixed to an axial direction extreme endmost surface of one of the inner and outer rings;

a core layer; and

an aluminum or alumina film disposed on said core layer.

2. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 1, further comprising:

~~a core layer;~~

~~an aluminum or alumina film disposed on said core layer; and~~

an adhesive layer further disposed on said aluminum or ~~aluminum~~ alumina film, said adhesive layer constituting the second portion.

3. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 2, wherein said sealing member is substantially formed into a circular shape.

4. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 3, wherein said sealing member is substantially formed into an annular shape.

5. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 3, wherein said sealing member has a ~~tub~~ knob portion which is outwardly protruded therefrom in an radial direction.

6. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 4, wherein said sealing member has a ~~tub~~ knob portion which is outwardly protruded therefrom in an radial direction.

7. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 4, wherein said sealing member has a ~~tub~~ knob portion which is inwardly protruded therefrom in an radial direction.

8. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 1, wherein the second portion is bonded and fixed to the axial direction end surface with a predetermined detachable bonding force.

9. (Withdrawn, Currently Amended) The ~~sealing member~~ rolling bearing according to claim 1, wherein the second portion is bonded and fixed to the axial direction end surface through an adhesive having a predetermined detachable bonding force which is lowerable when the adhesive is subject to an ultraviolet ray irradiation.

10. (Currently Amended) The ~~sealing member~~ rolling bearing according to claim 1, wherein the second portion is bonded and fixed to the axial direction end surface through an adhesive having a predetermined detachable bonding force which is lowerable when the adhesive is heated.

11-12. (Canceled)

13. (Withdrawn) A thin motor comprising:
a first member on which a stator is supported and fixed;
a second member on which a rotor facing the stator is supported and fixed; and
a rolling bearing relatively and rotatably combining said second member with said first member;

wherein the outer diameter size of the rotor is seven times or more as much as the axial direction size of the motor as a whole, and

wherein said rolling bearing comprises,

an inner ring;

an outer ring;

a plurality of rolling elements rotatably disposed therebetween and accommodated with a space which has at least one end part opening opened in the axial direction thereof and is formed between the inner circumferential surface of the outer ring and the outer circumferential surface of the inner ring; and

a sealing member including a first portion substantially covering at least a part of the end part opening of the space, and a second portion being bonded and fixed to the axial direction end surface of at least one of said inner and outer rings.

14. (Withdrawn) The thin motor according to claim 13, wherein said seal member comprises:

a core layer;

an aluminum or alumina film disposed on said core layer; and

an adhesive layer further disposed on said aluminum or alumina film, said adhesive layer constituting the second portion.

ant.
C1

15. (Currently Amended) A bearing device comprising:
an axis side member including a cylindrical part with an inner ring mounted externally,
and an outward flange part disposed on one end side in the axial direction;
a housing including a ring part with an outer ring mounted internally, and an outward
flange part disposed on the other end part in the axial direction;
a rolling bearing disposed between said axis side member and said housing and having an
outside surface covered by said outward flange part of said axis side member;
a sheet covering a gap between the inner ring and the outer ring and disposed externally
on an extreme endmost side of the other end part in the axial direction of the bearing device, the
sheet being bonded on at least one of the outward flange part of the housing, the inner ring and
the outer ring by a detachable bonding force,
wherein the detachable bonding force is lowerable when the bonded portion of the sheet
is heated.

16. (Withdrawn) The bearing device according to claim 15, wherein detachable force is
lowerable when the bonded portion of the sheet is subject to an ultraviolet ray irradiation.

17. (Canceled)

18. (New) A thin motor comprising:
a first member on which a stator is supported and fixed;
a second member on which a rotor facing the stator is supported and fixed; and
a rolling bearing, according to claim 1, relatively and rotatably combining said second
member with said first member.

19. (New) The thin motor according to claim 18, wherein the outer diameter size of the
rotor is seven times or more as much as the axial direction size of the motor as a whole.
